

Waterproof Outdoor 125khz Rfid Access Control Card Reader



PCD-103

Introduction

PCD-103E: 125KHz Proximity card reader

PCD-103M: 13.56MHz Mifare card reader

Features

- > 125KHz Proximity /13.56MHz Mifare Card Reader
- > Read Range: Up to 10CM(125KHz)/5CM(13.56MHz)
- > 26/34bit Wiegand (default)
- > Easy to install on Metal Door Frame or Mullion
- > External LED Control
- > External Buzzer Control
- > Indoor / Outdoor Operation
- > Solid Epoxy Potted
- > Waterproof IP65
- > Reverse Polarity Protection

Specifications

Read Range	PCD-103EM: Up to 10CM	Operating Temperature	-20° to +65°C
	PCD-103MF:Up to 5CM	Operating Humidity	10% to 90% relative humidity non-condensing
Reading Time (Card)	<=300ms	Colour	Black
Power / Current	DC 6-14V / Max.70mA	Material	ABS+PC with texture
Input Port	2ea	Dimension(W x H x T)mm	109 X 88.4 X34mm
Output Format	26bit/34bit Wiegand (default)	Weight	50g
LED Indicator	2 Colour LED Indicators(Red and Green)	Index of Protection	IP65

